





The New Standard in Overdenture Attachment Systems



Innovative Coating Technology Patented

Our patented fully biocompatible ceramic PVD (physical vapor deposition) coating provides many advantages over alternative abutment coatings.

Comprised of a tremendously hard layer of Zirconium Carbon Nitride (ZrCN), the abutment coating is more resistant to abrasion and wear compared to other common coatings. Additionally, its impressive rose gold tone blends well with the gingiva and provides a premium appearance.

Double Insert Connection

In addition to the compatible tri-lobe drive mechanism, Docklocs abutments feature the Bredent Torx® mechanism in the center of the abutment for simple seating using commonly available drivers. This ensures that the abutments meet the needs of a wide variety of clinicians without requiring the purchase of additional tooling.

Precision Retention Inserts

















These retention inserts have a lower tendency to absorb water and a high resistance to chemicals and fats, including alcoholic disinfectants. The inserts are extremely durable and have an excellent dynamic load capacity.



Docklocs Docklocs 18° Angled Abutment Straight Abutment

18° Angled Abutments

The availability of 18° angled abutments allows for the restoration of implants with up to 65° of divergence between them. This is a vast improvement over competitive systems that are not indicated for divergence over 20°. Further simplifying abutment placement are Docklocs indexing features and set screws, which allow angled abutments to be quickly and easily seated in the desired orientation.

Enhanced Denture Housings

The Docklocs Denture Cap has additional grooves and anti-rotational flat sections for improved retention and increased resistance to vertical and horizontal movements. The red anodized surface improves the aesthetics as grey titanium denture caps tend to shine through the surface of thin acrylic dentures.



Enhanced Denture Cap



HIGH PERFORMANCE POLYMER

Docklocs High Performance Polymer (HPP) Retention Inserts

Low tendency to absorb water and high resistance to chemicals and fats. Available in Processing Pack configurations or Replacement Packs in quantities of 8 per package. Conveniently packaged on trays for easy pickup with the Docklocs Universal Tool.





		Processing Pack (Standard), 0°-10° Processing Pack (Extended Pivot), 10°-20°
	REF	Description
	Pi	rocessing Packs with High Performance Polymer Retention Inserts
Divergence up to 10°	SKYDLHSP	Docklocs® HPP Standard Processing Set - 2 Set
Divergence up to 20°	SKYDLHEP	Docklocs® HPP Extended Processing Set - 2 Set
		Denture Caps
	SKYDLEDC	Docklocs® Enhanced Denture Cap 4 Pack
		Standard High Performance Polymer Retention Inserts 0° - 10°
		Standard High Performance Polymer Retention Inserts 0 - 10
Divergence up to 10°	SKYDLBLU	Docklocs® HPP Blue Insert 8 Pack
Divergence up to 10°	SKYDLBLU SKYDLPIN	
		Docklocs® HPP Blue Insert 8 Pack
	SKYDLPIN SKYDLCLR	Docklocs® HPP Blue Insert 8 Pack Doclocks® HPP Pink Insert 8 Pack
	SKYDLPIN SKYDLCLR	Docklocs® HPP Blue Insert 8 Pack Doclocks® HPP Pink Insert 8 Pack Docklocs® HPP Clear Insert 8 Pack
	SKYDLPIN SKYDLCLR Ext	Docklocs® HPP Blue Insert 8 Pack Doclocks® HPP Pink Insert 8 Pack Docklocs® HPP Clear Insert 8 Pack tended Pivot High Performance Polymer Retention Inserts 10° - 20°
up to 10°	SKYDLPIN SKYDLCLR Ext	Docklocs® HPP Blue Insert 8 Pack Docklocs® HPP Pink Insert 8 Pack Docklocs® HPP Clear Insert 8 Pack tended Pivot High Performance Polymer Retention Inserts 10° - 20° Docklocs® HPP Grey Insert 8 Pack

